

F.P.H. Art Metal Sp.j.

UI. Jabłoniowa 124, 83-331 Łapino Kartuskie, Poland Tel. 0048 58 681 80 78, Fax: 0048 58 681 80 64 www.art-metal.pl e-mail: biuro@art-metal.pl

Construction:


The fixture includes a threaded base (1) to which a tray (9) with an igniter module (2) and a lampholder (3) is attached. The igniter is normally hidden under a protective cover fitted to the tray. A RASTER reflector (5) can be used optionally. A bulb (6) is fitted into the lampholder. A threaded shade (7) is slid over the fixture and screwed into the female threaded base and, if appropriate, secured by set bolts.

Mounting instructions:

- *) -Attach the igniter (2) and the lampholder (3) to the base.
 - -lead the electrical cables out of the arm and place them neatly inside the fixture, connect them to the igniter (2).
 - -Place in position and attach the cover (4) of the igniter complete with the gasket (8).
 - -Attach the arm to the base (1).
 - -Put the bulb (6) in position.

If any lantern elements are supplied factory-mounted, the mounting stages marked with *) should be omitted (as this has already been done by the manufacturer)

TECHNICAL DATA:



Photometry (polar plot)

Power: ~230/50Hz

Protective class: I (\(\frac{1}{2}\))

IP65 -electrical part

IP65 -optical part














9


2


3

6









Туре	Light-producing element	Lamp holder	Weight [kg]	Pn [W]		Luminary dimensions
				IC	EB	Luminary aimensions
K1MH-70W	MH/HSI/HPI	E27	3,5	81	78	
K1MH-100W	MH/HSI/HPI	E27	4,0	114	109	
K1S-70W	WLS/SHP/SON	E27	3,5	81	78	
K1S-100W	WLS/SHP/SON	E40	4,1	114	109	
K1Z-E/Z	Bulb / MINI - LINX	E27	2,0	Max. 60		
						ØD _
						Wind area H/D A =0,13m ² 430/400

WARNING!! The weight of the unit may slightly differ for individual production batches.







