

F.P.H. Art Metal Sp.j.

UI. Jabłoniowa 124, 83-331 Łapino Kartuskie, Poland Tel. 0048 58 681 80 78, Fax: 0048 58 681 80 64 www.art-metal.pl e-mail: biuro@art-metal.pl

A5M FLORA

Construction;


The luminary is designed for mounting on a post or arm, ended with a 60mm diameter pin. The ceramic lamp holder E27 (2) is attached to the fixture body (1). The light source (3) is mounted vertical. The top is closed with a decorative lampshade (4).

Installation:

- *) -Connect the electrical cables to the holder (3).
 - -The body(1) place one the pole, lock position by screw.
 - -Place the light source (4) in the lamp holder (3).
 - -Put the shade (6) to the body (2), and twist.

If any lantern elements are supplied factory-mounted, the mounting stages marked with *) should be omitted (as this has already been done by the manufacturer)

TECHNICAL DATA:



Photometry (polar plot)

Sign:L-0A5M-01-00

Power: ~230/50Hz

Protective class: II

IP54 -electrical part

IP54 -optical part












4

ELECTRICAL DIAGRAM:



1.Incadescent bulb

Туре	Light-producing element	Lamp holder	Weight [kg]	Pn [W]	Luminary dimensions
A5M Z-E/Z	Bulb / MINI - LINX	E27	1,0	Maks. 60	
					Wind area L/D A =0,06m ² 300/270

WARNING!! The weight of the unit may slightly differ for individual production batches.

Last revision: 2020.01.23